



Interstellar

TWIN PHOTOELECTRIC BEAM SENSOR 2PH-15A

FEATURES :

- A.G.C. (Automatic Gain Control) Circuit.
- Rain, Dust & Insect Protection.
- Frost & Dew Protection.
- Adjustable Beam Interruption Period.



FEATURES



● A.G.C. Circuit


The A.G.C. (Automatic Gain Control) Circuit continually monitors for gradual changes in the signal's strength caused by weather conditions and adjusts the trigger level accordingly, to maintain proper sensitivity.

● Easy Installation

The pole mount brackets supplied will allow installation of two units on a pole at the same height easily.

● Adjustable Beam Interruption Period

Beam interruption time can be adjusted according to the peculiarities of each installation site. When protecting a wall or fence, a long interruption time will catch intruders, but let jumping cats or small objects pass through.



● Rain, Dust & Insect Protection


The rubber Ring and Rubber Grommets could prevent rain, dust and tiny insects from adversely affecting performance.



SPECIFICATION

Model	2PH-15A
Detection Range	Outdoor 45" (15m) or less Indoor 90" (30m) or less
Current Consumption	36mA 28VDC(Max)
Supply Voltage	10.5V-28VDC (Non-Polarity)
Detection System	Infrared Photoelectric
Infrared Beam	LED pulsed beam
Response Time	50-700 msec. (Adjustable)
Alarm Output	Dry connect relay NC./NO. 0.2A/DC28V Contact action: 0.5 sec to 2 secretary
Tamper Switch Output	Dry connect relay NC./NO. 0.2A/DC28V (N.C. opens when cover is removed.)
Alarm LED	Receiver : LED Red ON
Functions	Monitor jack output, AGC circuit, Frost proof cover.
Alignment Angle	Horizontal $\pm 90^\circ$; Vertical $\pm 10^\circ$
Operating Temperature	-13°F to +131°F (-25°C to + 55°C)
IP Rating	IP:54
Mounting Positions	Indoor / Outdoor
Wiring	Terminal
Weight	25 oz (708 grams)
Dimension (W x H x D)	2.85"x6.88"x2.9"
Cosmetic	PC (Burgundy color) 174.8x73.5 mm
Standard Accessories	Attenuation Sheet x1 pcs Screws (M4x20 Self Tapping) x 4 pcs Screws (M4x20) x4 pcs

DIMENSIONS



Unit : inch(mm)

NO.B2PH15A0811A

NOTE:

1. This unit is designed to detect an intruder and activate an alarm control panel. Being only a part of complete system, we cannot assume responsibility for theft or damages, should it occur.

2. Specifications and design are subject to change without prior notice.



Interstellar

Taiwan Security Net Co., Ltd. Designing / Manufacturing

No. 4-46 Feng Jen Rd, Kao Tarn Village,
Jen Wu Hsiang, Kaohsiung Hsian, Taiwan, R.O.C.
Tel : 886-7-3721111~3 Fax : 886-7-3721114

Web Site : <http://www.simos.com>
E-Mail : service@simos.com